

Terminales aisladas tipo "U"

Especificaciones

Sección principal: 0.5~1.5mm² (22~16) Corriente máxima: =19A

ITEM.NO.	Número de tornillo ANSI	Diámetro de boca de tornillo d2	B (mm)	L (mm)	F (mm)	H (mm)	DØ (mm)	Color
SV1.25-3	#4	3.2mm	5.7	21.2	6.5	10.0	4.3	Rojo
SV1.25-3.5	#6	3.7mm	5.7	21.2	6.5			
SV1.25-3.5	#6	3.7mm	6.4	21.2	6.5			
SV1.25-4	#8	4.3mm	6.4	21.2	6.5			
SV1.25-4	#8	4.3mm	7.2	21.2	6.5			
SV1.25-4	#8	4.3mm	8.1	21.2	6.5			
SV1.25-5	#10	5.3mm	8.1	21.2	6.5			
SV1.25-5	#10	5.3mm	9.5	21.2	6.5			
SV1.25-6	1/4	6.5mm	9.5	21.2	6.5			
SV1.25-6	1/4	6.5mm	12.0	21.2	11.0			

Sección principal: 1.5~2.5mm² (16~14) Corriente máxima: =27A

ITEM.NO.	Número de tornillo ANSI	Diámetro de boca de tornillo d2	B (mm)	L (mm)	F (mm)	H (mm)	DØ (mm)	Color
SV2-3	#4	3.2mm	5.7	21.2	6.5	10.0	4.9	Azul
SV2-3.5	#6	3.7mm	5.7	21.2	6.5			
SV2-3.5	#6	3.7mm	6.4	21.2	6.5			
SV2-4	#8	4.3mm	6.4	21.2	6.5			
SV2-4	#8	4.3mm	7.2	21.2	6.5			
SV2-4	#8	4.3mm	8.1	21.2	6.5			
SV2-5	#10	5.3mm	8.1	21.2	6.5			
SV2-5	#10	5.3mm	9.5	21.2	6.5			
SV2-6	1/4	6.5mm	9.5	21.2	6.5			
SV2-6	1/4	6.5mm	12.0	12.0	11.0			

Sección principal: 2.5~4mm² (14~12) Corriente máxima: =37A

ITEM.NO.	Número de tornillo ANSI	Diámetro de boca de tornillo d2	B (mm)	L (mm)	F (mm)	H (mm)	DØ (mm)	Color
SV3.5-4	#8	4.3mm	8.0	24.8	7.0	12.5	6.2	Negro
SV3.5-5	#10	5.3mm	8.0	24.8	7.0			
SV3.5-6	1/4	6.5mm	12.0	28.0	12.1			

Sección principal: 4~6mm² (12~10) Corriente máxima: =48A

ITEM.NO.	Número de tornillo ANSI	Diámetro de boca de tornillo d2	B (mm)	L (mm)	F (mm)	H (mm)	DØ (mm)	Color
SV5.5-3.5	#6	3.7mm	8.3	25.2	7.5	12.5	6.7	Amarillo
SV5.5-4	#8	4.3mm	8.3	25.2	7.5			
SV5.5-4	#8	4.3mm	9.0	23.9	7.5			
SV5.5-5	#10	5.3mm	9.0	23.9	7.5			
SV5.5-6	1/4	6.5mm	9.0	23.9	7.5			
SV5.5-6	1/4	6.5mm	12.0	31.2	12.0			
SV5.5-8	5/16	8.4mm	14.0	30.0	11.5			

