

RAMCROil - INSTRUMENTATION Cable

For standard applications, flame retardant, UV resistant

Multi-Core, HT 105°-Insulation, Collective Screen, Hi-PVC-Sheath

MAS3706HBACX-T-UL

Application

These cables are designed to connect electronic instrumentation, analog and digital signal circuits. This cable does not spread flame to the top of the tray in the Vertical-Tray Flame Test in UL 1685.

Construction

		Unit	Nominal Value
Formation	1 triads		
Section	20AWG		
Conductor	Tinned copper wire, 7 strands	mm	0,90
Insulation	Hi Temperature polyvinyl chloride - PVC HT 105°C	mm	1,50
Colour Code	black - white - red		
Individual Screen	N.A.		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	0,026 mm Aluminium / PETP tape over tinned copper drain wire		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Hi Temperature polyvinyl chloride - PVC HT 105°C - Grey	mm	5,20
Cable Printing	RAMCRO Italy Type TC - 1x3x20AWG CU cl.2/PVC/CAM/PVC 600V MIL UL1581 105°C month/15 + batch n° + meter marking		

Technical Data & Standard References

Fire Propagation:		
- Test on single cable	IEC 60332-1	Construction Reference Standard: Type of Cable:
- Test on bunched cables	IEC 60332-3	
- Vertical Tray Flame Test	UL1685	
Limiting Oxygen Index (LOI)	ASTM D 2863 (min 30%)	Other References: - NEC code, sec. 725 PLTC, - NEC code, sec. 727 ITC, - UL 1685 - ASTM D 1239 - NF C 32-020 - IRAM IAP - IEC 79-14
Flammability temperature (FT)		
Amount of halogen acid gas	IEC 60754-10	
Sunlight resistance	UL 1581 section 1200	
Notes		

Electrical & Mechanical Data

Conductor Cross-section	Nom.	20AWG	Temperature Range:	
DC Resistance per core at 20° C	max	Ω/km	During Operation	° C -30° C up to +105°C
Insulation Resistance at 20° C	min	MΩ*km	During Installation	° C -5° C up to +50°C
Mutual Capacitance	max	nF/km	Min. Bending Radius	mm 6 x cable diameter
Inductance	max	mH/km		
Test Voltage - Core/Core	V	2000		
Test Voltage - Core/Screen	V	2000		
L/R Ratio	max	μH/Ω		
Operating Voltage	V	600		

Issued by: sabrina

Prepared by RAMCRO Tech

Creator: LDG

Via Marzorati, 15 - 20014 Nerviano - Milan - Italy / www.ramcro.it

Transfer to third parties only under authorization by Ramcro S.p.A.

Printing errors excepted. Subject to alterations.



Date of issue:

29/09/2014 00:00

Form 1