

UTP3300TFL-II Series Linear DC Power Supply

◆ Introduction

UTP3000TFL-II series single-channel linear DC power supplies are economical benchtop tools for DIY electronics hobbyists, electronics manufacturing and testing, and other applications.



◆ Features

- Light weight and concise interface
- 1-channel linear DC power supplies feature
- High-precision 4-digit voltage and current display, 10mV/1mA
- Low ripple/noise
- Auto conversion of constant voltage and current with current limit protection

◆ UTP3300TFL-II

Technical index

Model	UTP3313TFL-II	UTP3315TFL-II								
Output voltage	0~30V	0~30V								
Output current	0~3A	0~5A								
Output power	90W	150W								
Load regulation	CV≤0.01%+3mV, CC≤0.1%+5mA	CV≤0.01%+5mV, CC≤0.1%+10mA								
Programming accuracy (25°C±5°C)	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="padding: 2px;">Voltage</td> <td style="padding: 2px;">< 0.5%+20mV</td> </tr> <tr> <td style="padding: 2px;">Current</td> <td style="padding: 2px;">< 0.5%+5mA</td> </tr> </table>	Voltage	< 0.5%+20mV	Current	< 0.5%+5mA	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="padding: 2px;">Voltage</td> <td style="padding: 2px;">< 0.5%+20mV</td> </tr> <tr> <td style="padding: 2px;">Current</td> <td style="padding: 2px;">< 0.5%+10mA</td> </tr> </table>	Voltage	< 0.5%+20mV	Current	< 0.5%+10mA
Voltage	< 0.5%+20mV									
Current	< 0.5%+5mA									
Voltage	< 0.5%+20mV									
Current	< 0.5%+10mA									
Ripple and noise	≤1mVrms	≤2mVrms								
Output regulate resolution	CV: 10mV (typical), CC: 1mA (typical)									
Reliability	MTBF(e): ≥2000hrs									
Display mode	LED voltage and current dual display									

General Characteristics

Power	Input voltage: 110V/220V±5% AC, Frequency: 50Hz/60Hz	
Product net weight	3kg	4kg
Product size (W×H×D)	105mm x 165mm x 249mm	
Standard quantity per carton	4pcs	
Standard carton size	330mm x 285mm x 460mm	
Standard carton gross weight	14kg	
17kg		

Ordering Information

UTP3300TFL-II Series	Linear DC Power Supply (1-Channel, 30V, 5A, 10mV, 1mA)	UTP3315TFL-II
	Linear DC Power Supply (1-Channel, 30V, 3A, 10mV, 1mA)	UTP3313TFL-II
Standard Accessories	International standard power cord	
	Test output line	