

Fully Vinyl Insulated Disconnecter

Specifications

Lead section: 0.5~1.5mm²(22~16) Max current: =10A


ITEM.NO.	Meme Tab (mm)	Dimension (mm)				
		W	B	DØ	dØ	L
FDFD1.25-187(5)	0.5 x 4.75	5.6	3.28	4.0	1.7	20.0
FDFD1.25-187(8)	0.8 x 4.75	5.6	3.28	4.0	1.7	20.0
FDFD1.25-250	0.8 x 6.35	7.4	3.28	4.0	1.7	21.5

Lead section: 1.5~2.5mm²(16~14) Max current: =15A

ITEM.NO.	Meme Tab (mm)	Dimension (mm)				
		W	B	DØ	dØ	L
FDFD2-187(5)	0.5 x 4.75	5.6	5.0	4.5	2.3	20.0
FDFD2-187(8)	0.8 x 4.75	5.6	5.0	4.5	2.3	20.0
FDFD2-250	0.8 x 6.35	7.4	5.0	4.5	2.3	21.5

Lead section: 4~6mm²(12~10) Max current: =24A

ITEM.NO.	Meme Tab (mm)	Dimension (mm)				
		W	B	DØ	dØ	L
FDFD5.5-250	0.8 x 6.35	7.4	6.6	5.7	3.4	25.5



Piggy Back Disconnecter

Specifications

Lead section: 0.5~1.5mm²(22~16) Max current: =10A

ITEM.NO.	Meme Tab (mm)	Dimension (mm)					
		B	B1	B	DØ	dØ	L
PBDD1.25-250	0.8 x 6.35	7.4	6.3	10.0	3.8	1.7	21.5

Lead section: 1.5~2.5mm²(16~14) Max current: =15A

ITEM.NO.	Meme Tab (mm)	Dimension (mm)					
		B	B1	B	DØ	dØ	L
PBDD2-250	0.8 x 6.35	7.4	6.3	10.0	4.3	2.3	21.5

Lead section: 4~6mm²(12~10) Max current: =24A

ITEM.NO.	Meme Tab (mm)	Dimension (mm)					
		B	B1	B	DØ	dØ	L
PBDD5.5-250	0.8 x 6.35	7.4	6.3	14.0	5.7	3.4	25.0

